

APPENDIX B
BUILDING CODE SUMMARY FOR ALL COMMERCIAL PROJECTS
(except one- and two-family dwellings and townhouses)
(Reproduce the following data on the building plans sheet 1 or 2)

Name of Project: _____
Address: _____ Zip Code _____
Proposed Use: _____
Owner/Authorized Agent: _____ Phone # (____) ____ - _____ E-Mail _____
Owned By: City/County Private State
Code Enforcement Jurisdiction: City _____ County _____ State

LEAD DESIGN PROFESSIONAL: _____

DESIGNER	FIRM	NAME	LICENSE #	TELEPHONE #	E-MAIL
Architectural	_____	_____	_____	(____) _____	_____
Civil	_____	_____	_____	(____) _____	_____
Electrical	_____	_____	_____	(____) _____	_____
Fire Alarm	_____	_____	_____	(____) _____	_____
Plumbing	_____	_____	_____	(____) _____	_____
Mechanical	_____	_____	_____	(____) _____	_____
Sprinkler-Standpipe	_____	_____	_____	(____) _____	_____
Structural	_____	_____	_____	(____) _____	_____
Retaining Walls >5' High	_____	_____	_____	(____) _____	_____
Other	_____	_____	_____	(____) _____	_____

2006 EDITION OF NC CODE FOR: New Construction Addition Upfit
EXISTING: Reconstruction Alteration Repair
CONSTRUCTED _____ ORIGINAL USE _____ RENOVATED _____ CURRENT USE _____

BUILDING DATA

Construction Type: I-A II-A III-A IV V-A
 I-B II-B III-B V-B
Mixed construction: No Yes Types _____

Sprinklers: No Partial Yes NFPA 13 NFPA 13R NFPA 13D
Standpipes: No Yes Class I II III Wet Dry
Fire District: No Yes Flood Hazard Area: No Yes
Building Height: Feet _____ Number of Stories _____
Mezzanine: No Yes
Gross Building Area:

Floor	Existing (sq ft)	New (sq ft)	Sub-Total
6th Floor	_____	_____	_____
5th Floor	_____	_____	_____
4th Floor	_____	_____	_____
3rd Floor	_____	_____	_____
2nd Floor	_____	_____	_____
Mezzanine	_____	_____	_____
1st Floor	_____	_____	_____
Basement	_____	_____	_____
Total	_____	_____	_____

APPENDIX B

ALLOWABLE AREA

Primary Occupancy: Assembly A-1 A-2 A-3 A-4 A-5
 Business Educational Factory F-1 Moderate F-2 Low
 Hazardous H-1 Detonate H-2 Deflagrate H-3 Combust H-4 Health H-5 HPM
 Institutional I-1 I-2 I-3 I-4
 I-3 Condition 1 2 3 4 5
 Mercantile Residential R-1 R-2 R-3 R-4
 Storage S-1 Moderate S-2 Low High-piled
 Utility and Miscellaneous Parking Garage Open Enclosed Repair Garage

Secondary Occupancy: _____
 Special Uses: 402 403 404 405 406 407 408 409 410 411 412
 413 414 415 416 417 418 419 420 421

Special Provisions: 508.2 508.3 508.4 508.5 508.6 508.7
 Mixed Occupancy: No Yes Separation: _____ Hr. Exception: _____

- Incidental Use Separation (302.1.1)
This separation is not exempt as a Non-Separated Use (see exceptions).
- Non-Separated Use (302.3.1)
The required type of construction for the building shall be determined by applying the height and area limitations for each of the applicable occupancies to the entire building. The most restrictive type of construction, so determined, shall apply to the entire building.
- Separated Use (302.3.2) - See below for area calculations

For each story, the area of the occupancy shall be such that the sum of the ratios of the actual floor area of each use divided by the allowable floor area for each use shall not exceed 1.

$$\frac{\text{Actual Area of Occupancy A}}{\text{Allowable Area of Occupancy A}} + \frac{\text{Actual Area of Occupancy B}}{\text{Allowable Area of Occupancy B}} = \leq 1$$

$$\text{-----} + \text{-----} + \text{-----} = \leq 1.00$$

STORY NO.	DESCRIPTION AND USE	(A) BLDG AREA PER STORY (ACTUAL)	(B) TABLE 503 ⁵ AREA	(C) AREA FOR FRONTAGE INCREASE ²	(D) AREA FOR SPRINKLER INCREASE ²	(E) ALLOWABLE AREA OR UNLIMITED ³	(F) MAXIMUM BUILDING AREA ⁴

- 1 Frontage area increases from Section 506.2 are computed thus:
 - a. Perimeter which fronts a public way or open space having 20 feet minimum width = _____ (F)
 - b. Total Building Perimeter = _____ (P)
 - c. Ratio (F/P) = _____ (F/P)
 - d. W = Minimum width of public way = _____ (W)
 - e. Percent of frontage increase $I_f = 100 [F/P - 0.25] \times W/30 = \text{-----} (\%)$
- 2 The sprinkler increase per Section 506.3 is as follows:
 - a. Multi-story building $I_s = 200$ percent
 - b. Single story building $I_s = 300$ percent
- 3 Unlimited area applicable under conditions of Sections Group B, F, M, S, A-4 (507); Group A motion picture (507.9); Malls (402.6); and H-2 aircraft paint hangers (507.7).
- 4 Maximum Building Area = total number of stories in the building x E (506.4).
- 5 The maximum area of parking garages must comply with 406.3.5. The maximum area of air traffic control towers must comply with 412.1.2.

ALLOWABLE HEIGHT

	ALLOWABLE (TABLE 503)	INCREASE FOR SPRINKLERS	SHOWN ON PLANS	CODE REFERENCE
Type of Construction	Type _____		Type _____	
Building Height in Feet	Feet _____	Feet = H + 20' = _____		
Building Height in Stories	Stories _____	Stories + 1 = _____	Stories	

FIRE PROTECTION REQUIREMENTS

Life Safety Plan Sheet #, if Provided _____

BUILDING ELEMENT	FIRE SEPARATION DISTANCE (FEET)	RATING		DETAIL # AND SHEET #	DESIGN # FOR RATED ASSEMBLY	DESIGN # FOR RATED PENETRATION	DESIGN # FOR RATED JOINTS
		REQ'D	PROVIDED (W/ * REDUCTION)				
Structural Frame, including columns, girders, trusses							
Bearing Walls							
Exterior							
North							
East							
West							
South							
Interior							
Nonbearing Walls and Partitions							
Exterior walls							
North							
East							
West							
South							
Interior walls and partitions							
Floor Construction including supporting beams and joists							
Roof Construction including supporting beams and joists							
Shaft Enclosures - Exit							
Shaft Enclosures - Other							
Corridor Separation							
Occupancy Separation							
Party/Fire Wall Separation							
Smoke Barrier Separation							
Tenant Separation							
Incidental Use Separation							

* Indicate section number permitting reduction

LIFE SAFETY SYSTEM REQUIREMENTS

Emergency Lighting:	<input type="checkbox"/> No	<input type="checkbox"/> Yes	
Exit Signs:	<input type="checkbox"/> No	<input type="checkbox"/> Yes	
Fire Alarm:	<input type="checkbox"/> No	<input type="checkbox"/> Yes	
Smoke Detection Systems:	<input type="checkbox"/> No	<input type="checkbox"/> Yes	<input type="checkbox"/> Partial _____
Panic Hardware:	<input type="checkbox"/> No	<input type="checkbox"/> Yes	

EXIT REQUIREMENTS
Number and arrangement of exits

FLOOR, ROOM OR SPACE DESIGNATION	MINIMUM ² NUMBER OF EXITS		TRAVEL DISTANCE		ARRANGEMENT MEANS OF EGRESS ^{1,3} (SECTION 1014.2)	
	REQUIRED	SHOWN ON PLANS	ALLOWABLE TRAVEL DISTANCE (TABLE 1015.1)	ACTUAL TRAVEL DISTANCE SHOWN ON PLANS	REQUIRED DISTANCE BETWEEN EXIT DOORS	ACTUAL DISTANCE SHOWN ON PLANS

1. Corridor dead ends (Section 1016.3).
2. Single exits (Table 1018.2).
3. Common Path of Travel (Section 1013.3).

EXIT WIDTH

USE GROUP OR SPACE DESCRIPTION	(a)	(b)	CALCULATED OCCUPANT LOAD	(c)	EXIT WIDTH (in) ^{2,3,4,5,6}				
	AREA ¹ sq. ft.	AREA ¹ PER OCCUPANT (TABLE 1004.1.2)		EGRESS WIDTH PER OCCUPANT (TABLE 1005.1)	REQUIRED WIDTH (SECTION 1005.1) (a, b) c	ACTUAL WIDTH SHOWN ON PLANS			

- For SI: 1 inch = 25.4 mm, 1 square foot = 0.929m².
1. See Table 1004.1.2 to determine whether net or gross area is applicable. See definition "Area, Gross" and "Area, Net" (Section 1002).
 2. Minimum stairway width (Section 1009.1); min. corridor width (Section 1016.2); min. door width (Section 1008.1).
 3. Minimum width of exit passageway (Section 1020.2).
 4. See Section 1004.5 for converging exits.
 5. The loss of one means of egress shall not reduce the available capacity to less than 50 percent of the total required (Section 1005.1).
 6. Assembly occupancies (Section 1024).

STRUCTURAL DESIGN

DESIGN LOADS:

Importance Factors: Wind (IW) _____
 Snow (IS) _____
 Seismic (IE) _____

Live Loads: Roof _____ psf
 Floor _____ psf

Snow Load: _____ psf
 Exposure Factor (Ce) _____ Thermal Factor (C+) _____

Wind Load: Basic Wind Speed _____ mph (ASCE-7-02)
 Exposure Category _____
 Wind Base Shears (for MWFRS) $V_x =$ _____ $V_y =$ _____

SEISMIC DESIGN CATEGORY A

Compliance with Section 1616.4 only? Yes No
SEISMIC DESIGN CATEGORY B C D

Provide the following Seismic Design Parameters:

Seismic Use Group _____

Spectral Response Acceleration S_s _____ %g S_1 _____ %g

Site Classification _____ Field Test Presumptive Historical Data

Basic structural system (check one)
 Bearing Wall Dual w/Special Moment Frame
 Building Frame Dual w/Intermediate R/C or Special Steel
 Moment Frame Inverted Pendulum

Seismic base shear $V_x =$ _____ $V_y =$ _____

Analysis Procedure _____ Simplifies _____ Equivalent Lateral Force _____ Modal

Architectural, Mechanical, Components anchored? _____

LATERAL DESIGN CONTROL: Earthquake _____ Wind _____

SOIL BEARING CAPACITIES:

Field Test (provide copy of test report) _____ psf
 Presumptive Bearing capacity _____ psf
 Pile size, type, and capacity _____

PLUMBING FIXTURE REQUIREMENTS

USE	WATERCLOSETS		URINALS	LAVATORIES		SHOWERS/ TUBS	DRINKING FOUNTAINS	
	MALE	FEMALE		MALE	FEMALE		REGULAR	ACCESSIBLE
EXISTING								
NEW								
REQUIRED								

ACCESSIBILITY PARKING

LOT OR PARKING AREA	TOTAL # OF PARKING PLACES		# OF ACCESSIBLE SPACES PROVIDED		TOTAL # ACCESSIBLE PROVIDED
	REQUIRED	PROVIDED	REGULAR WITH 5' ACCESS AISLE	VAN SPACES WITH 8' ACCESS AISLE	
TOTAL					

SPECIAL APPROVALS

Special approval: (Local Jurisdiction, Department of Insurance, OSC, DPI, DFS, ICC, etc., describe below)

ENERGY SUMMARY

ENERGY REQUIREMENTS:

The following data shall be considered minimum and any special attribute required to meet the energy code shall also be provided. Each designer shall furnish the required portions of the project information for the plan data sheet. If energy cost budget method, state the annual energy cost budget vs allowable annual energy cost budget.

THERMAL ENVELOPE

Method of Compliance:

Prescriptive Performance Energy Cost Budget

Roof/ceiling Assembly (each assembly)

Description of assembly

U-Value of total assembly

R-Value of insulation

Skylights in each assembly

U-Value of skylight

total square footage of skylights in each assembly

Exterior Walls (each assembly)

Description of assembly

U-Value of total assembly

R-Value of insulation

Openings (windows or doors with glazing)

U-Value of assembly

shading coefficient

projection factor

low *e* required, if applicable

Door *R*-Values

Walls adjacent to unconditioned space (each assembly)

Description of assembly

U-Value of total assembly

R-Value of insulation

Openings (windows or doors with glazing)

U-Value of assembly

Low *e* required, if applicable

Door *R*-Values

Walls below grade (each assembly)

Description of assembly

U-Value of total assembly

R-Value of insulation

Floors over unconditioned space (each assembly)

Description of assembly

U-Value of total assembly

R-Value of insulation

Floors slab on grade

Description of assembly

U-Value of total assembly

R-Value of insulation

Horizontal/vertical requirement

slab heated

ELECTRICAL SUMMARY

ELECTRICAL SYSTEM AND EQUIPMENT

Method of Compliance:

 Prescriptive Performance Energy Cost Budget
Lighting schedule

lamp type required in fixture
 number of lamps in fixture
 ballast type used in the fixture
 number of ballasts in fixture
 total wattage per fixture
 total interior wattage specified vs allowed
 total exterior wattage specified vs allowed

Equipment schedules with motors (not used for mechanical systems)

motor horsepower
 number of phases
 minimum efficiency
 motor type
 # of poles

MECHANICAL SUMMARY

MECHANICAL SYSTEMS, SERVICE SYSTEMS AND EQUIPMENT

Method of Compliance

 Prescriptive Performance Energy Cost Budget

Climate Zone _____

Thermal Zone _____

winter dry bulb
 summer dry bulb

Interior design conditions

winter dry bulb
 summer dry bulb
 relative humidity

Building heating load**Building cooling load****Mechanical Spacing Conditioning System**

Unitary
 description of unit
 heating efficiency
 cooling efficiency
 Heat output of unit
 cooling output of unit

Boiler

total boiler output. If oversized, state reason.

Chiller

total chiller capacity. If oversized, state reason.

List equipment efficiencies**Equipment schedules with motors** (mechanical systems)

motor horsepower
 number of phases
 minimum efficiency
 motor type
 # of poles

